

## 500W Single Output Mini-size Series



- Compact size, high reliability
- Built-in fan speed control
- 100% full load burn-in test
- Protections: over current/ over voltage/ over temperature/ short circuit
- 1 year warranty
- F630 241 x 124 x 65(mm)

AC input voltage range .....	170~264VAC (210~370VDC)
Input frequency .....	47~63Hz
Inrush current .....	60A/230V
Input leakage current .....	< 0.7mA/ 230VAC
Line regulation (full load) .....	≤ ± 0.5%
Output voltage adjust range .....	± 10%
Output over current protection .....	110~130%
Output over voltage protection .....	115~150%
Withstand voltage .....	I/P -O/P: 1.5KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise time .....	50ms@full load (typical)
Hold up time .....	20ms@full load (typical)
Operating temp. & humidity .....	-10°C~+50°C, 20%~90%RH (non condensing)
Storage temp. & humidity .....	-20°C~+85°C, 20%~95%RH (non condensing)
Safety standards .....	design meet GB4943, UL60950, EN60950
EMC standards .....	design meet GB9254, EN55022 classA
Cooling method .....	fan

Model	DC Output		Load regul.	R&N	Efficiency
HF500W-SM-5	5V	80A	1.0%	150mV	76%
HF500W-SM-12	12V	42A	0.5%	150mV	82%
HF500W-SM-24	24V	21A	0.5%	150mV	84%
HF500W-SM-48	48V	10A	0.5%	240mV	86%

\* 3~48VDC output all available.

## Drawing

