

480W Single Output Series - with PFC



- Universal AC input / full range
- PF>0.98@115VAC; >0.95@230VAC
- Built in remote sense
- Remote ON/OFF control
- Protections: over current/ over voltage/ over temperature/ short circuit
- 2 years warranty
- F648C 278 x 127 x 43(mm)

AC input voltage range	85~264VAC (120~370VDC)
Input frequency	47~63Hz
Inrush current	cold start, 20A/115VAC, 40A/230VAC
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	≤ ± 0.5%
Output voltage adjust range	± 10%
Output over current protection	110~130%, current limiting, auto recovery
Output over voltage protection	115~150%
Withstand voltage	I/P-O/P: 3.0KVAC/1min; I/P-F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise, Hold up time	50ms, 20ms@full load (typical)
Operating temp. & humidity	-10°C~+50°C, 20%~93%RH (non condensing)
Storage temp. & humidity	-20°C~+85°C, 20%~95%RH (non condensing)
Safety standards	design meet GB4943, UL60950, EN60950
EMC standards	design meet GB9254, EN55022 classB EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	fan

Model	DC Output		Load regul.	R&N	Efficiency
HF480W-SC-3.3	3.3V	85A	0.5%	100mV	73%
HF480W-SC-5	5V	85A	0.5%	100mV	79%
HF480W-SC-12	12V	43A	0.5%	100mV	85%
HF480W-SC-15	15V	35A	0.5%	100mV	85%
HF480W-SC-24	24V	22A	0.5%	150mV	87%
HF480W-SC-48	48V	11A	0.5%	240mV	89%

* 3~48VDC output all available.